

OMNI FLOOR ANCHOR SYSTEMS

All OMNI Floor Anchor Systems feature stainless steel or aluminum materials designed for demanding transportation environments. It has always been recommended that tie-downs match with the brand of their floor anchorages. Now with the OMNI series you can reduce your liability and know that your products are tested and certified for both Q'Straint and Sure-Lok systems.

WARNING

Using OMNI anchorages and track make it possible to use both Q'Straint and Sure-Lok tiedowns. Every retractor in a wheelchair position must be EITHER from Q'Straint or Sure-Lok -- never mix brand on a four-point securement. OMNI anchorages are strictly tested and certified to be used with approved Q'Straint and Sure-Lok systems. Other non-approved systems should not be used with OMNI anchorages at any time.

FE750NA100-04-3

Regular Series L-Track Pre-Drilled

- 100" (254cm) in length
- Standard 82 degree countersunk holes are pre-drilled every 4" (102mm)
- Accommodates 5/16" (8mm) bolts



FE752NA100-04-3

Surface Angled Series L-Track Pre-Drilled

- 100" (254cm) in length
- Standard 82 degree countersunk holes are pre-drilled every 4" (102mm)
- Accommodates 5/16" (8mm) bolts



FE753NA100-04-3

Flange Series L-Track Pre-Drilled

- 100" (254cm) in length
- Standard 82 degree countersunk holes are pre-drilled every 4" (102mm)
- Accommodates 5/16" (8mm) bolts

